

EXPLORER

TAS
FLOORING

GLUE DOWN | 5 MM, 20 MIL



Columbus | DJLV0301Z



Drake | DJLV0303Z



Shackleton | DJLV0308



Cook | DJLV0309



Kingsley | DJLV0310



Harrison | DJLV0311

SPECIFICATIONS

Construction	Luxury Vinyl Plank
Classification	ASTM F1700, Class III, Type B
Dimensions	7" Wide x 48" Long, 177.8 mm x 1219.2 mm
Overall Thickness	5 mm including Rubber Backing
Wear Layer	20 mil High-Density Polyurethane
Finish Coat	Enhanced Ceramic Bead Coating
Texture	Embossed
Edge Profile	4-Sided Square Edge
Packaging	23.35 sf/ctn, 50 ctn/plt, 1167.5 sf/plt
Installation	Glue Down, Loose Lay
Warranty	15 Year Light Commercial, 15 Year MultiFamily, Limited Lifetime Residential

INSTALLATION FAST FACTS

- Acclimate to Normal Room Conditions (NRC) 65°F - 85°F
- Expansion Space: 1/4" gap
- Ambient RH Between 35% to 60%
- Work out of several boxes, mixing product for visual appearance

Read Complete Instructions Before Installing



tascontract.com

SPEC SHEET
WARRANTY
INSTALLATION & MAINTENANCE
TRIMS, TRANSITIONS & [QNOSE](#)



Additional specifications, full installation/maintenance and warranty information available online at TASCONTRACT.COM.

TAS
CONTRACT

TAS supply company, Inc.