PROVINCIAL ESTATE



SPC 6.0 MM, 20 MIL

| Construction | SPC, Stone Polymer Composite, Rigid Core | |
|-------------------|--|--|
| Classification | ASTM F3261, Class 1, Type B, Grade 1, Class B | |
| Dimensions | 7" Wide x 60" Long, 180 mm x 1524 mm | |
| Overall Thickness | 6.0 mm (Includes 1 mm pad) | |
| Attached Pad | 1 mm IXPE Sound Abatement Pad | |
| Wear Layer | 20 mil | |
| Finish Coat | High-Definition, Low Gloss Matte | |
| Texture | Embossed-in-Register | |
| Edge Profile | 4-Sided Painted Bevel | |
| Packaging | 23.62 sf/carton - 45 cartons/pallet - 1062.9 sf/pallet | |

Installation & Maintenance

Angle / Angle, Float

Layout Room size: 1/4" Expansion required at perimeter and at all vertical surfaces. Transition required for rooms larger than 50' W x 50' L.

Ambient & Surface Temperature at installation: 60 - 85 degrees Fahrenheit

Maintenance: No Polish

| Test Method & Requirements | | |
|---|------------------|------------------|
| Resilient Floor in Modular Format | ASTM F3261 | Pass |
| Thickness (with Pad) | ASTM F386/ (387) | Pass |
| Wear Layer Thickness | ASTM F410 | Pass |
| Stain/Chemical Resistance | ASTM F925 | Pass |
| Resistance to Heat Color Change | ASTM F1514 | Pass |
| Resistance to Light Color Change | ASTM F1515 | Pass |
| Residual Indentation | ASTM F1914 | Pass |
| Size & Squareness | ASTM F2055 | Pass |
| Dimensional Stability w/Exposure to Heat | ASTM F2199 | Pass |
| Dimensional Stability w/Exposure to Heat | ISO 23999 | Pass |
| Determination of Geometrical Characteristics | ISO 24337 | Pass |
| Static Coefficient of Friction Polished Surface | ASTM D2047 | Exceeds Standard |
| Static Load Limit | ASTM F970 | PASS >250 LBS |
| Flammability/Radiant Flux | ASTM E648 | Class I |
| Smoke Density | ASTM E662 | Pass |
| Impact Insulation Class IIC | ASTM E492* | |
| Sound Transmission Class STC | ASTM E90* | |

^{*}The flooring assembly dictates IIC, STC, HIIC, and Low IIC results; contact your representative for specific testing.

Health & Environmental

FloorScore Certified

Phthalate-Free
















Warranty

10 Yr Light Commercial, 10 Yr Multi-Family, 30 Yr Residential, No Sheen Guarantee

Accessories

Trims: T Mold, Reducer, End Cap, Stair Nose, Quarter Round

ONose Stair Nosing

