

# TANDEM CRESCENDO



WPC | 8.0 MM, 20 MIL



**Toscanini** | DGWP0501



**Figaro** | DGWP0502



**Carman** | DGWP0503



**Luicia** | DGWP0504



**Falstaff** | DGWP0505



**Aida** | DGWP0506



**Rigoletto** | DGWP0507

## SPECIFICATIONS

Construction	WPC Rigid Core (Wood Plastic Composite)
Classification	ASTM F3261, Class I, Type B, Grade 1, Class B
Dimensions	5" Wide x 60" Long (125 mm x 1500 mm)
Overall Thickness	8.0 mm (Includes 1.5 mm IXPE Pad)
Wear Layer	20 mil
Finish Coat	Adamantine Finish™ Scratch, Stain, Wear Resist
Texture	Embossed-In-Register
Edge Profile	Painted Bevel
Packaging	14.13 sf/ctn, 7 pcs/ctn, 21.1 lbs/ctn, 98 ctn/plt, 1384.7 sf/plt
Installation	Angle/Angle
Warranty	10 Year Light Commercial, 10 Year Multifamily, 30 Year Residential

## INSTALLATION FAST FACTS

- Transitions required in rooms over 50' x 50' or 875 sf
- Acclimate to Normal Room Conditions (NRC) 65°F - 85°F
- Expansion Space: 1/4" gap
- Ambient RH Between 35% to 60%
- Work out of several boxes, mixing product for visual appearance
- Hydro Radiant Heat approved (≤ 85°F)

Read Complete Instructions Before Installing



SPEC SHEET, WARRANTY  
INSTALLATION & MAINTENANCE

tascontract.com

