



**Norse Peak** | WILSPC0701



**Cascade** | WILSPC0702



**Halifax** | WILSPC0703



**Livingston** | WILSPC0704



**Riverside** | WILSPC0705



**Tamarac** | WILSPC0706



**Glacier Bay** | WILSPC0707



**Wind River** | WILSPC0708

## SPECIFICATIONS

Construction	LSPC Rigid Core, Light Stone Polymer Composite
Classification	ASTM F3261
Dimensions	9" Wide x 60" Long, 226 mm x 1517 mm
Overall Thickness	7.5 mm (includes 1.5 mm Pad)
Wear Layer	20 mil
Finish Coat	Adamantine Finish
Texture	Embossed-In-Register
Edge Profile	4-Sided Pressed Bevel
Packaging	29.52 sf/ctn, 8 pcs/ctn, 53.3 lbs/ctn, 40 ctn/plt, 1,180.8 sf/plt
Installation	Angle/Angle
Warranty	10 year light commercial, 10 year multifamily, 30 year residential

## INSTALLATION FAST FACTS

- Radiant Heat: Approved (Hydro Systems ONLY)
- Acclimate product to normal room conditions
- Recommended Room Temp: 60°F-85°F after install
- Expansion Space: 1/4" gap
- Transition required for rooms larger than 50'W x 50'L
- Subfloors dry and flat (3/16" in 10')

Read Complete Instructions Before Installing



tascontract.com

**SPEC SHEET  
WARRANTY  
INSTALLATION & MAINTENANCE  
TRIMS, TRANSITIONS & QNOSE**

