

# RESONATE



SPC | 5.0 MM, 20 MIL



**Ash** | SCRC0201



**Craft Oak** | SCRC0202



**Hickory** | SCRC0203



**Vernessa Oak** | SCRC0204



**Remmy Oak** | SCRC0205



**Walnut** | SCRC0206



**Acacia** | SCRC0207



**Warm Oak** | SCRC0208

## SPECIFICATIONS

Construction	SPC, Stone Polymer Composite, Rigid Core
Classification	ASTM F3261, Class I, Type B, Grade 1, Class B
Dimensions	7" Wide X 48" Long
Overall Thickness	5.0 mm (Includes 1 mm IXPE pad)
Wear Layer	20 MIL
Finish Coat	Low Gloss, Polyurethane
Texture	Smooth
Edge Profile	4-Sided Painted Bevel
Packaging	18.88 sf/ctn, 65 ctn/plt, 1227.2 sf/plt
Installation	Angle/Angle
Warranty	10 Yr Light Commercial, 10 Yr Multi-Family, 30 Yr Residential

## INSTALLATION FAST FACTS

- Radiant Heat: Approved (Hydro Systems ONLY)
- Acclimate product to normal room conditions
- Recommended Room Temp: 60°F-85°F after install
- Expansion Space: 1/4" gap
- Transition required for rooms larger than 50'W x 50'L
- Subfloors dry and flat (3/16" in 10')

Read Complete Instructions Before Installing



tasflooring.com

**SPEC SHEET  
WARRANTY  
INSTALLATION & MAINTENANCE  
TRIMS, TRANSITIONS & QNOSE**



Additional Specifications, Full Installation Instructions & Warranty Information Available Online at [TASFLOORING.COM](https://www.tasflooring.com)

A division of **TAS** supply company, Inc.