

## New York Collection

### Technical Data

#### Description

The New York Collection is a high performance matting line that is made from 100% premium polyamide nylon fibers with a premium vinyl backing. Coarse fibers effectively brush shoes clean and absorb moisture, while providing a carpet-like appearance.

#### General Information

This product must be used for interior applications only and be installed by professional installers that have sufficient professional liability insurance coverage (aka Errors and Omissions Insurance) for the project. Matter Surfaces recommends installing and maintaining entrance matting at all outdoor entrances; this will improve air quality, reduce maintenance costs, and lengthen the life of your floors.

Proper glides must be used on all furniture that may slide directly across the floor. Heavy objects must not be moved directly across the floor; use protective boards.

Direct sunlight can cause UV damage (fading or bleaching) to most interior finishes, so Low E glass should be selected that will reduce the UV transmission to less than 1%. If not, applying 3M™ protection film (or similar) on the windows is recommended. Areas of the flooring subjected to direct sunlight, for example through doors or windows, must be covered using blinds, curtains, cardboard or similar materials for 2 hours before, during, and for a period of 72 hours after the installation.

|                                                                                                                                                                                      |                                                                                                                                                          |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Sizes, Weights &amp; Units</b>                                                                                                                                                    | 6'7" wide x 82' long rolls.                                                                                                                              |
| Custom lengths available. Pile thickness is 1/4-inch, and the overall thickness is 3/8-inch. Pile weight of 29.5 oz./yd <sup>2</sup> with a total weight of 99.0 oz./yd <sup>2</sup> |                                                                                                                                                          |
| <b>Adhesive &amp; Coverage</b>                                                                                                                                                       | <p>MI 1000 Adhesive, coverage is approximately 150 - 175 sq. ft. / gal.</p> <p>Liquid Cold Weld, coverage is approximately 200 linear feet per tube.</p> |
| MI 1000 Adhesive using a 1/32 inch x 1/16 inch x 1/32 inch U-notched trowel (FFA). Coverage will depend on substrate and conditions.                                                 |                                                                                                                                                          |
| <b>Note:</b> All seams require welding with liquid weld, details are in the Installation Instructions.                                                                               |                                                                                                                                                          |