



Cache | DGWP0301



Pendleton | DGWP0302



Prestige | DGWP0303



Essence | DGWP0304



Monaco | DGWP0305



Mystique | DGWP0306



Castlewood | DGWP0307

SPECIFICATIONS

Construction	Engineered Vinyl Click (EVC), Waterproof Core
Classification	ASTM F3261
Dimensions	9" Wide x 60" Long, 225 mm x 1500 mm
Overall Thickness	10 mm (includes 2.0 mm pad)
Attached Pad	2.0 mm Quiet Cork
Wear Layer	22 mil
Finish Coat	Adamantine Scratch/Stain/Wear Resist
Texture	Wood Embossed
Edge Profile	4-Sided Painted Bevel
Packaging	21.8 sf/ctn, 6 pc/ctn, 43.6 lb/ctn, 48 ctn/plt, 1046.4 sf/plt
Warranty	30 Year Residential; 10 Year Light Commercial
Installation	Angle/Angle

INSTALLATION FAST FACTS

- Transitions required in rooms over 25' x 35' or 875 sf
- Acclimate to Normal Room Conditions (NRC) 65°F - 85°F
- Expansion Space: 1/4" gap
- Ambient RH Between 35% to 60%
- Work out of several boxes, mixing product for visual appearance
- Hydro Radiant Heat approved (≤ 85°F)
- Minimum 3500 PSI for Concrete/Cypcrete Substrates

Read Complete Instructions Before Installing



tasflooring.com

**SPEC SHEET
WARRANTY
INSTALLATION & MAINTENANCE
TRIMS, TRANSITIONS & QNOSE**

