OLYMPUS

TAS FLOORING

EVC | 10 MM, 22 MIL



Cache | DGWP0301



Pendleton | DGWP0302



Essence | DGWP0304



Monaco | DGWP0305



Banff | DGWP0308



Ajax | DGWP0309



Viceroy | DGWP0310

SPECIFICATIONS

Construction	Engineered Vinyl Click (EVC), Waterproof Core
Classification	ASTM F3261
Dimensions	9" Wide x 60" Long (225 mm x 1500 mm)
Overall Thickness	10 mm (includes 2.0 mm pad)
Attached Pad	2.0 mm Quiet Cork
Wear Layer	22 mil
Finish Coat	Super Matte w/Adamantine Finish®
Texture	Embossed
Edge Profile	4-Sided Painted Bevel
Packaging	21.8 sf/ctn, 6 pcs/ctn, 43.88 lbs/ctn, 48 ctn/plt, 1046.4 sf/plt
Warranty	10 Year Light Commercial, 30 Year Residential
Installation	Angle/Angle

INSTALLATION FAST FACTS

- Transitions required in rooms over 50'x50' or 2500 sf
- Acclimate to Normal Room Conditions (NRC) 65°F - 85°F
- Expansion Space: 1/4" gap
- Ambient RH Between 35% to 60%
- Work out of several boxes, mixing product for visual appearance
- Hydro Radiant Heat approved (≤ 85°F)
- Minimum 3500 PSI for Concrete/Gypcrete Substrates

Read Complete Instructions Before Installing

tasflooring.com

SPEC SHEET
WARRANTY
INSTALLATION & MAINTENANCE
TRIMS, TRANSITIONS & QNOSE

floor score
SCScertified
PHTHALATE FREE
Waterproof
Cork Backing
Painted Bevel
Adamantine Finish®