

CLEAN STEP



24 OZ, 100% SOLUTION DYED NYLON

Construction	PVC Free, Four Layers: Non-Woven Primary Layer Advanced Polymer Pre-Coat Modified Bitumen Core Polyester Felt Back
Tile Dimensions	19.7" x 19.7", 50 cm x 50 cm
Weight	24 oz, 815 g/m ²
Gauge	1/12"
Density oz/yd ³	7500 oz
Packaging	20 tiles/carton - 32 carton/pallet

Installation & Maintenance

Glue Down Adhesive: Taylor Versatile or Dynamic, SprayLock 6500

Follow CRI Carpet Installation Guidelines

Test Method & Requirements

Usage Classification	33 (EN1307)	
Flammability	ASTM E648 EN13051-1	Class I Bfl-s1
Static	AATCC134	<2 kV

Health & Environmental

CRI Green Label Plus # GLP1215

100% PVC Free


Up to 20% Pre-Consumer Recycled Content

Warranty

Lifetime Commercial

Stain Resistance, Backing Performance, Wear

Layout Options:



Quarter Turn

Installation Fast Facts

Follow CRI Carpet Installation Standards and Guidelines
Inspect new flooring prior to installation
Always work from several boxes
Clean up spills immediately
Use floor protection for furniture
Read complete instructions before installing



tascontract.com

Additional Info
Warranty
Installation & Maintenance

