SAVVY LIVING

TAS FLOORING



Samatha | DGRC1003



Ronald | DGRC1004



Barney | DGRC1007*



Cayuse | DGRC1008*



Brookline | DGRC1009*



Waddel | DGRC1010*



Caroll | DGRC1011*



Crockett | DGRC1012*

SPECIFICATIONS

Construction	SPC Rigid Core, Stone Polymer Composite
Classification	ASTM F3261
Dimensions	7" Wide x 60" Long, 181 mm x 1524 mm *7" Wide x 56" Long, 180 mm x 1420 mm
Overall Thickness	6.0 mm (includes 1.0 mm IXPE Pad)
Wear Layer	22 mil
Finish Coat	Adamantine Finish™
Texture	Embossed-In-Register
Edge Profile	Pressed Bevel
Packaging	60" Plank - 23.62 sf/ctn, 8 pcs/ctn, 50.5 lbs/ctn, 45 ctn/plt, 1069.2 sf/plt *56" Plank - 24.76 sf/ctn, 10 pcs/ctn, 51.5 lbs/ctn, 45 ctn/plt, 1114.2 sf/plt
Installation	Angle/Angle
Warranty	10 Year Light Commercial, 10 Year Multifamily, 30 Year Residential

INSTALLATION FAST FACTS

- Radiant Heat: Approved (Hydro Systems ONLY)
- Acclimate product to normal room conditions
- Recommended Room Temp: 60°F-85°F after install
- Expansion Space: 1/4" gap
- Transition required for rooms larger than 50'W x 50'L
- Subfloors dry and flat (3/16" in 10')

Read Complete Instructions Before Installing

tascontract.com

SPEC SHEET
WARRANTY
INSTALLATION & MAINTENANCE
TRIMS, TRANSITIONS & QNOSE

floor score
SCScertified
PHTHALATE FREE
Waterproof
Hydronic Heat
Large Install
Adamantine Finish™

TAS CONTRACT

Additional specifications, full installation/maintenance and warranty information available online **TASCONTRACT.COM**

A division of T&A supply company, Inc.