

Superior Dimensional Stability

The Rigid Core ABA structure provides a enhanced dimensional stability in areas prone to issues related to expansion and contraction.

Specifications

Dimensions (nominal) 4.5 mm thick overall x 7.25" W x 48" L

Construction 3.5 mm core plus 1 mm attached IXPE pad

Polyurethane + Anti-Microbial &

Anti-Scratch Coating

Wear Layer 12 m

Texture Embossed

Edge Profile 4-Sided Painted Bevel

Installation Angle/Angel

25 Yr Residential, 5 Yr Light Commercial, Warranty

5 Yr Multi-Family

Packaging 28.84 sf/ctn, 55 ctn/plt, 1586.2 sf/plt

DID YOU KNOW?



LOCALLY STOCKED IN KENT, WA

Acclaim is stocked heavily in Kent, WA. What you need, when you need it.



ABA CONSTRUCTION

The ABA layered construction of Acclaim provides superior dimensional stability in a rigid core product.



PEACE OF MIND ANTI-MICROBIAL COATING

Our anti-microbial coating prevents the growth and spreading of mold and bacteria on top of the floor.



COMFORT **UNDER FOOT**

Premium attached IXPE pad reduces sound transfer, provides for an easy and quick installation and adds comfort underfoot.



marketingta@tasupply.com tasflooring.com 6807 South 216th St Kent, WA 98032



A Division of

