TYSON

TAS FLOORING

SPC | 5.0 MM, 12 MIL



Chalus Hazelwood | PPRC0101



Davos Oak | PPRC0102



Fenwick Oak | PPRC0103



Beacon Oak | PPRC0107



Alcove Oak | PPRC0108



Medallion Oak | PPRC0109



Nordland Hickory | PPRC0110



Collins | PPRC0111



Appalachian Oak | PPRC0112



Allendale Hickory | PPRC0113



Thomasville Hickory | PPRC0114



Jatoba | PPRC0115

SPECIFICATIONS

Construction	SPC Rigid Waterproof Core Vinyl Click
Classification	ASTM F3261
Dimensions	7" wide x 48" long, 182 mm x 1220 mm
Overall Thickness	5 mm (includes 1 mm IXPE Pad)
Wear Layer	12 mil
Finish Coat	Polyurethane, Matte
Texture	Embossed
Edge Profile	4-Sided Micro Bevel
Packaging	28.68 sf/ctn, 12 pcs/ctn, 48.5 lbs/ctn, 55 ctn/plt, 1577.4 sf/plt
Installation	Angle/Angle
Warranty	5 Year Light Commercial, 25 Year Multifamily (units), 5 Year Multifamily (common areas) & 25 Year Residential

INSTALLATION FAST FACTS

- Radiant Heat: Approved (Hydro Systems ONLY)
- Acclimate product to normal room conditions
- Recommended Room Temp: 60°F-85°F after install
- Expansion Space: 1/4" gap
- Transition required for rooms larger than 50'W x 50'L
- Subfloors dry and flat (3/16" in 10')

Read Complete Instructions Before Installing

tascontract.com

SPEC SHEET
WARRANTY
INSTALLATION & MAINTENANCE
TRIMS, TRANSITIONS & QNOSE

floor score SCScertified | Waterproof | Rigid Core | PHTHALATE FREE

Additional specifications, full installation/maintenance and warranty information available online

TAS CONTRACT

tascontract.com | a division of T&A supply company, Inc.