



Eagledale | SCRC0101



Windsong | SCRC0102



Blakley | SCRC0103



Windslow | SCRC0104



Hawley | SCRC0105



Fletcher | SCRC0106



Tracyton | SCRC0107



Ferncliff | SCRC0108

SPECIFICATIONS

Construction	SPC Rigid Core, Stone Polymer Composite
Dimensions	9" Wide x 60" Long, 228 mm x 1524 mm
Overall Thickness	6.0 mm (includes 1.5 mm pad)
Wear Layer	20 mil
Finish Coat	Polyurethane
Texture	Embossed
Edge Profile	4-Sided Painted Bevel
Installation	Angle / Angle
Warranty	30 Yr Residential, 10 Yr Light Commercial, 10 Yr Multi-Family,
Packaging	22.44 sf/carton - 56 carton/pallet - 1256.6 sf/pallet
Testing	IIC 62, STC 62 on Concrete w/Drop Ceiling

INSTALLATION FAST FACTS

- Radiant Heat: Approved (Hydro Systems ONLY)
- Acclimate product to normal room conditions
- Recommended Room Temp: 60°F-85°F after install
- Expansion Space: 1/4" gap
- Transition required for rooms larger than 50'W x 50'L
- Subfloors dry and flat (3/16" in 10')

Read Complete Instructions Before Installing



tasflooring.com

SPEC SHEET
WARRANTY
INSTALLATION & MAINTENANCE
TRIMS, TRANSITIONS & [QNOSE](#)

