

EQUINOX MULTI



LAMINATE 12 MM + 1.5 MM EVA ATTACHED PAD



Landau | CH50101390003



Skyway | CH50101785002



Hampton | CH50101795002



Charlot | CH50101810003



Countryside | CH5010770005



Riviera | CH5010773009



Schooner | CH5011000004



Stonehill | CH5011271007

SPECIFICATIONS

Construction	12 mm Water Resistant Standard Core + 1.5 mm EVA Attached Pad
Dimensions	3.5", 5.5", 7.5" Wide x 48" Long, 92 mm, 144 mm, 196 mm x 1213 mm
Overall Thickness	13.5 mm (includes 1.5 mm pad)
Wear Surface	AC4
Texture	EIR or Embossed
Edge Profile	4-Sided Painted Bevel
Installation	Angle / Drop & Tap
Warranty	Lifetime Residential, 15 Yr Light Commercial, 15 Yr Multi-Family
Packaging	22.54 sf/carton - 33 carton/pallet - 743.81 sf/pallet

INSTALLATION FAST FACTS

- Radiant Heat: Approved (Hydro Systems ONLY)
- Acclimate product to normal room conditions
- Relative Humidity: 35%-55%
- Recommended Room Temp: 60°F-85°F after install
- Transitions required for rooms larger than 25'L or 35"W
- Subfloors dry and flat (3/16" in 10')
- Installation on or below grade concrete requires 6 mil moisture barrier

Read Complete Instructions Before Installing



tasflooring.com

**SPEC SHEET
WARRANTY
INSTALLATION & MAINTENANCE
TRIMS, TRANSITIONS & QNOSE**



72 Hour Topical

Additional Specifications, Full Installation Instructions & Warranty Information Available Online

tasflooring.com | a division of **TAS** supply company, Inc.