

ABA 4.5 MM, 12 MIL



Tanunda Hickory | WIRC1501



Lager Hickory | WIRC1502



Porter Hickory | WIRC1503



Erdinger Oak | WIRC1504



Yebinna Oak | WIRC1505



Calla Acacia | WIRC1506

SPECIFICATIONS

Construction	ABA Rigid Core, Stone Polymer Composite
Classification	ASTM F3261, Class I, Type B, Grade 1, Class B
Dimensions	7.25" Wide x 48" Long, 183 mm x 1220 mm
Overall Thickness	5.5 mm (Includes 1.5 mm Pad)
Wear Layer	12 mil
Finish Coat	Adamantine Finish™ Scratch, Stain, Wear Resist
Texture	Embossed
Edge Profile	4-Sided Painted Bevel
Packaging	26.43 sf/ctn, 11 pcs/ctn, 45.7 lbs/ctn, 60 ctn/plt, 1585.8 sf/plt
Installation	Angle / Angle, Float
Warranty	5 Yr Light Commercial, 5 Yr Multi-Family, 25 Yr Residential

INSTALLATION FAST FACTS

- Transitions required for rooms larger than 50' W x 50' L
- Acclimate to Normal Room Conditions (NRC) 60°F - 85°F
- Hydro Radiant Heat approved (≤ 85°F)
- Expansion Space: 1/4" gap
- Ambient RH Between 35% to 55%
- Floor Flatness to 1/8" in 6'
- Floating floors must be allowed to expand and contract with no restrictions

Read Complete Instructions Before Installing



tasflooring.com

SPEC SHEET
WARRANTY
INSTALLATION & MAINTENANCE

