

PVC-FREE GLUE DOWN | 2.5 MM



Adair Plank | NOLUP250404



Bollen Plank | NOLUP250401



Oriell Plank | NOLUP250406



Rowan Plank | NOLUP250407



Saddle Plank | NOLUP250403



Vernon Plank | NOLUP250402



Tatum Plank | NOLUP250405



Sinatra Stone | NOLUT250421

SPECIFICATIONS

Construction	PVC -Free Resilient Plank & Tile
Classification	ASTM3404
Dimensions (nominal)	Wood: 7" Wide x 48" Long, 177.8 mm x 1219.2 mm Stone: 12" Wide x 24" Long, 308.8 mm x 609.6 mm
Overall Thickness	2.5 mm
Finish Coat	PVC-Free Polyurethane and Thermoplastic Polyurethane
Texture	Embossed
Edge Profile	Square Edge
Packaging	Wood: 35 sf/ctn, 15 pcs/ctn, 30.5 lbs/ctn, 60 ctn/plt, 2100 sf/plt Stone: 36 sf/ctn, 18 pcs/ctn, 31.3 lbs/ctn, 60 ctn/plt, 2160 sf/plt
Warranty	10 Year Commercial, 10 Year Light Commercial, 25 Year Residential
Installation	Glue Down

INSTALLATION FAST FACTS

- Acclimate to Normal Room Conditions (NRC) 60°F - 85°F, RH Between 35% - 55%
- RH Between 35% - 55%
- Hydro Radiant Heat approved (≤ 85°F)
- Roll flooring immediately after installation in two directions, reroll 2 hours later
- Follow adhesive instructions for substrate moisture, coverage, PH, porosity, and open time
- Repair or replace worn trowel notches
- Insure floor flatness to within 1/8" in 6'

Read Complete Instructions Before Installing



tascontract.com

**SPEC SHEET
WARRANTY
INSTALLATION & MAINTENANCE**

