

WATERPROOF LAMINATE | 9.5 MM + 1.5 MM PAD



Brighthon | CH5011271007



Broadmoor | CH5011193011



Sandstone | CH5011270008



Karsten | CH50101660002



Shadow Creek | CH50101768002



Aldarra | CH50102043002

SPECIFICATIONS

Construction	Waterproof Core Laminate
Classification	EN 13329
Dimensions	6.5" Wide x 48" Long
Overall Thickness	9.5 mm (includes 1.5 mm Pad)
Wear Surface	AC4 Rating
Texture	Embossed-In-Register, Advanced Texturing
Edge Profile	4-Sided Painted Bevel
Packaging	21.64 sf/carton - 24 cartons/pallet - 973.8 sf/pallet
Installation	Angle / Drop & Tap
Warranty	15 Yr Light Commercial, 15 Yr Multi-Family, Lifetime Residential

INSTALLATION FAST FACTS

- Radiant Heat: Approved (Hydro Systems ONLY)
- Acclimation: 48 hrs unopened carton
- Moisture Content: Not to Exceed 2.5%
- Expansion Space: 3/8" gap
- Transitions not required in rooms up to 66' w or 66' long
- Inspect flooring prior to installation
- Use floor protection for furniture

Read Complete Instructions Before Installing



tasflooring.com

**SPEC SHEET
WARRANTY
INSTALLATION & MAINTENANCE
TRIMS, TRANSITIONS & QNOSE**

"Our AtroGuard Core is more dense and resistant to swelling. TightLock blocks water from penetrating the floor for at least 72 hours. The attached 1.5mm pad reduces noise transfer and adds comfort underfoot."

