

GLUE DOWN | 3.5 MM, 12 MIL



**Nordic** | NOLVA0801



**Amity** | NOLVA0802



**Bryce** | NOLVA0803



**Ventura** | NOLVA0804



**Anastasia** | NOLVA0805



**Whitman** | NOLVA0806



**Solaris** | NOLVA0807

## SPECIFICATIONS

Construction	Luxury Vinyl Tile
Dimensions	7" Wide x 48" Long (177.8 mm x 1219.2 mm)
Overall Thickness	3.5 mm (Includes 1.0 mm Pad)
Wear Layer	12 mil
Finish	Polyurethane
Texture	Embossed
Edge Profile	Square Edge
Installation	Glue Down
Warranty	5 Year Light Commercial, 5 Year Multifamily Common Area, 25 Year Residential
Packaging	32.67 sf/ctn, 14 pcs/ctn, 30.4 lbs/ctn, 50 ctn/plt, 1633.5 sf/plt

## INSTALLATION FAST FACTS

- Acclimate to Normal Room Conditions (NRC) 60°F - 85°F, RH Between 35% - 55%
- Hydro Radiant Heat approved (≤ 85°F)
- Roll flooring immediately after installation in two directions, reroll 2 hours later
- Follow adhesive instructions for substrate moisture, coverage, PH, porosity, and open time
- Repair or replace worn trowel notches
- Insure floor flatness to within 1/8" in 6'

Read Complete Instructions Before Installing



tasflooring.com

SPEC SHEET, WARRANTY  
INSTALLATION & MAINTENANCE

