



Adalynn | PPLV0305



Barnhart | PPLV0304



Collier | PPLV0307



Crossroads | PPLV0301



McKenzie | PPLV0303



Noelle | PPLV0308



Rolands | PPLV0302



Warden | PPLV0306

SPECIFICATIONS

Construction	Luxury Vinyl Tile
Dimensions	7.25" Wide x 48" Long, 184 mm x 1219 mm
Overall Thickness	5.0 mm (includes 1.5 mm EVA Pad)
Wear Layer	12 mil
Finish	UV-Polyurethane
Texture	Embossed
Edge Profile	4-Sided Micro Bevel
Installation	Glue Down
Warranty	5 Year Light Commercial & Multi-Family Common Area 25 Year Residential & Multi-Family Residence Units
Packaging	24.16 sf/ctn - 65 ctn/plt - 1570.4 sf/plt

INSTALLATION FAST FACTS

- Acclimate to Normal Room Conditions (NRC) 60°F - 85°F, RH Between 35% - 55%
- Do not net or compression fit
- Minimum 3500 PSI for Concrete/Gypsum
- Hydro Radiant Heat approved (≤ 85°F)
- Roll flooring immediately after installation in two directions, reroll 2 hours later
- Follow adhesive instructions for substrate moisture, coverage, PH, porosity, and open time
- Repair or replace worn trowel notches
- Insure floor flatness to within 1/8" in 6'

Read Complete Instructions Before Installing



tasflooring.com

SPEC SHEET
WARRANTY
INSTALLATION & MAINTENANCE
TRIMS, TRANSITIONS & [QNOSE](#)

