

WATERPROOF LAMINATE AC3 | 8 MM + 2.0 MM PAD



Kindrid | DWLA0101



Whist | DWLA0102



Solace | DWLA0103



Haven | DWLA0104



Repose | DWLA0105



Mystic | DWLA0106



White Horizon | DWLA0107

SPECIFICATIONS

Construction	Waterproof Laminate
Classification	EN13329
Dimensions	7.75" Wide x 48" Long (196 mm x 1215 mm)
Overall Thickness	10 mm (Includes 2 mm IXPE Pad)
Wear Surface	AC3 Rating
Texture	Standard
Edge Profile	4-Sided Painted Bevel
Packaging	30.785 sf/ctn, 12 pcs/ctn, 47.84 lbs/ctn, 30 ctn/plt, 923.6 sf/plt
Installation	Angle/Angle
Warranty	Waterproof, 25 Year Residential

INSTALLATION FAST FACTS

- Radiant Heat: Approved (Hydro Systems ONLY)
- Acclimate product to normal room conditions
- Leave 3/8" expansion for areas over 25'
- Transitions required for rooms larger than 45'L or 45"W
- Subfloors dry and flat (3/16" in 10')
- Installation on or below grade concrete requires 6 mil moisture barrier

Read Complete Instructions Before Installing



tasflooring.com

SPEC SHEET, WARRANTY
INSTALLATION & MAINTENANCE
TRIMS, TRANSITIONS & [QNOSE](#)

