

COMPLIMENT

SPC | 5.0 MM, 12 MIL



Norwood | WIRC0701



Cortez | WIRC0702



Spice Road | WIRC0703



Salathe | WIRC0704



Half Dome | WIRC0705



Stonebrook | WIRC0706



Fjord | WIRC0708

SPECIFICATIONS

Construction	Rigid Core, Stone Polymer Composite
Classification	ASTM F3261, Class 1, Type B, Grade 1, Class B
Dimensions	7.25" Wide x 48" Long, 183 mm x 1220 mm
Overall Thickness	5.0 mm (Includes 1 mm IXPE Pad)
Wear Layer	12 mil
Finish Coat	Polyurethane
Texture	Embossed
Edge Profile	4-Sided Micro Bevel
Packaging	24.031 sf/ctn, 10 pcs/ctn, 41.6 lbs/ctn, 50 ctn/plt, 1201.55 sf/plt
Installation	Angle / Angle, Float
Warranty	5 Year Light Commercial, 5 Year Multifamily, 25 Year Residential

INSTALLATION FAST FACTS

- Radiant Heat: Approved (Hydro Systems ONLY)
- Acclimate product to normal room conditions
- Recommended Room Temp: 60°F-85°F after install
- Expansion Space: 1/4" gap
- Transition required for rooms larger than 50'W x 50'L
- Subfloors dry and flat (3/16" in 10')

Read Complete Instructions Before Installing



tasflooring.com

**SPEC SHEET
WARRANTY
INSTALLATION & MAINTENANCE
TRIMS, TRANSITIONS & QNOSE**

