

BUILDER'S SELECT

TAS
FLOORING

SPC | 5.0 MM, 20 MIL



Caruso | DGRC1101



Bocelli | DGRC1102



Fleming | DGRC1103



Seneca | DGRC1104



Bianco | DGRC1105

SPECIFICATIONS

Construction	SPC Rigid Core
Classification	ASTM F3261, Class I, Type B, Grade 1, Class B
Dimensions	9" Wide x 60" Long (228 mm x 1500 mm)
Overall Thickness	5.0 mm
Wear Layer	20 mil
Finish Coat	Polyurethane
Texture	Embossed
Edge Profile	Painted Bevel
Packaging	22.09 sf/ctn, 6 pcs/ctn, 37.7 lbs/ctn, 52 ctn/plt, 1148.7 sf/plt
Installation	Angle/Angle
Warranty	10 Year Light Commercial, 10 Year Multifamily, 30 Year Residential

INSTALLATION FAST FACTS

- No Transitions in under 2,500 sf
- Acclimate to Normal Room Conditions (NRC) 65°F - 85°F
- Hydro Radiant Heat approved ($\leq 85^{\circ}\text{F}$)
- Expansion Space: 1/4" gap
- Ambient RH Between 35% to 60%
- Work out of several boxes, mixing product for visual appearance
- Hydro Radiant Heat approved ($\leq 85^{\circ}\text{F}$)
- Structurally Sound

Read Complete Instructions Before Installing



tascontract.com

SPEC SHEET
WARRANTY
INSTALLATION & MAINTENANCE
TRIMS, TRANSITIONS & QNOSE



TAS
CONTRACT