

EXPEDITION

GLUE DOWN | 2.0 MM, 12 MIL



Norwood | WILV1301



Cortez | WILV1302



Spice Road | WILV1303



Salathe | WILV1304



Half Dome | WILV1305



Stonebrook | WILV1306



Fjord | WILV1308

SPECIFICATIONS

Construction	Luxury Vinyl Tile
Classification	ASTM F1700, Class III, Type B
Dimensions	7" Wide x 48" Long, 177.8 mm x 1220 mm
Overall Thickness	2.0 mm
Wear Layer	12 mil
Finish Coat	Polyurethane
Texture	Embossed
Edge Profile	Micro-Bevel
Packaging	35.023 sf/ctn, 15 pcs/ctn, 28.4 lbs/ctn, 70 ctn/plt, 2451.6 sf/plt
Installation	Glue Down
Warranty	5 Year Light Commercial, 25 Year Multifamily Residence Units, 25 Year Residential

INSTALLATION FAST FACTS

- Acclimate to Normal Room Conditions (NRC) 60°F - 85°F, RH Between 35% - 65%
- Do not net or compression fit
- Hydro Radiant Heat approved (≤ 85°F)
- Roll flooring immediately after installation in two directions, reroll 2 hours later
- Follow adhesive instructions for substrate moisture, coverage, PH, porosity, and open time
- Repair or replace worn trowel notches
- Ensure floor flatness to within 1/8" in 6'

Read Complete Instructions Before Installing



**SPEC SHEET
WARRANTY
INSTALLATION & MAINTENANCE**

tasflooring.com

