

# EXPEDITION



GLUE DOWN | 2.0 MM, 12 MIL



**Norwood** | WILV1301



**Cortez** | WILV1302



**Spice Road** | WILV1303



**Salathe** | WILV1304



**Half Dome** | WILV1305



**Stonebrook** | WILV1306



**Fjord** | WILV1308

## SPECIFICATIONS

Construction	Luxury Vinyl Tile
Classification	ASTM F1700, Class III, Type B
Dimensions	7" Wide x 48" Long, 177.8 mm x 1220 mm
Overall Thickness	2.0 mm
Wear Layer	12 mil
Finish Coat	Polyurethane
Texture	Embossed
Edge Profile	Micro-Bevel
Packaging	35.023 sf/ctn, 15 pcs/ctn, 28.4 lbs/ctn, 70 ctn/plt, 2451.6 sf/plt
Installation	Glue Down
Warranty	5 Year Light Commercial, 25 Year Multifamily Residence Units, 25 Year Residential

## INSTALLATION FAST FACTS

- Acclimate to Normal Room Conditions (NRC) 60°F - 85°F, RH Between 35% - 65%
- Do not net or compression fit
- Minimum 3500 PSI for Concrete/Gypsum
- Hydro Radiant Heat approved ( $\leq 85^{\circ}\text{F}$ )
- Roll flooring immediately after installation in two directions, reroll 2 hours later
- Follow adhesive instructions for substrate moisture, coverage, PH, porosity, and open time
- Repair or replace worn trowel notches
- Ensure floor flatness to within 1/8" in 6'

**Read Complete Instructions Before Installing**



**SPEC SHEET  
WARRANTY  
INSTALLATION & MAINTENANCE**

[tasflooring.com](https://tasflooring.com)



SCS certified



Additional Specifications, Full Installation Instructions & Warranty Information Available Online

[tasflooring.com](https://tasflooring.com) | a division of **TAS** supply company, Inc.