




Heritage Hickory | NE450702



Cappucino Oak | NE450703



Modern Hickory | NE450500



Imperial Khaki | NE450704



Modern Taupe | NE450706




Vanilla Hickory | NE450503

SPECIFICATIONS

Construction:	DropFit Loose Lay with Fiberglass Reinforcement
Dimension:	9.25" Wide x 60.25" Long
Overall Thickness:	4.5 mm
Wear Layer:	20 mil
Finish:	Polyurethane
Texture:	Embossed
Edge Profile:	4-sided micro bevel
Packaging:	23.22 sf/ctn, 60 ctn/plt, 1393.2 sf/plt
Installation:	DropFit Loose Lay with perimeter adhesive or full spread adhesive
Warranty:	Lifetime Waterproof, Lifetime Residential Wear, 20-Year Commercial Wear
Testing:	Critical Radiant Flux ASTM E468 Class I Surface Flammability DOC FF 1-70 Passed Coefficient of Friction ASTM 2047 Passed>0.6

FEATURES	BENEFITS
Loose Lay or gluedown installation	Installation options provide flexibility depending on the project
Fiberglass stabilization layer	Provides dimensional stability and added strength to the core
Waterproof	For peace of mind spills and splashes



(800) 345-6287 | info@pacmat.com

Call your local sales rep for additional specifications, full installation instructions, and warranty information.