VISTA TILE



SPC | 5.0 MM, 12 MIL

Construction	SPC Rigid Core, Stone Polymer Composite	
Classification	ASTM F3261, Class I, Type B, Grade 2, Class B	
Dimensions	12" Wide x 24" Long, 305 mm X 610 mm	
Overall Thickness	5.0 mm (Includes 1.0 mm Pad)	
Attached Pad	1.0 mm IXPE Acoustical Pad	
Wear Layer	12 mil	
Finish Coat	Polyurethane	
Texture	Embossed	
Edge Profile	4-Sided Painted Bevel	
Packaging	24.03 sf/ctn, 12 pcs/ctn, 42 lbs/ctn, 54 ctn/plt, 1298 sf/plt	



Angle / Angle

Layout Room size: Minimum expansion space to all vertical substrates 1/4" Transition required for rooms larger than 50' W x 50' L.

Ambient & Surface Temperature at installation: 60 - 85 degrees Fahrenheit

Maintenance: No Polish, Fresh Floors by TAS Flooring

Test Method & Requirements		
Resilient Floor in Modular Format	ASTM F3261	Pass
Thickness (with Pad)	ASTM F386/387	Pass
Wear Layer Thickness	ASTM F410	Pass
Stain/Chemical Resistance	ASTM F925	Pass
Resistance to Heat Color Change	ASTM F1514	Pass
Resistance to Light Color Change	ASTM F1515	Pass
Residual Indentation	ASTM F1914	Pass
Size & Squareness	ASTM F2055	Pass
Dimensional Stability	ASTM F2199	Pass
Dimensional Stability w/Exposure to Heat	ISO 23999	Pass
Determination of Geometrical Characteristics	ISO 24337	Pass
Static Coefficient of Friction Polished Surface	ASTM D2047	Exceeds
Static Load Limit	ASTM F970	0.005 in or less 2,000 ps
Flammability/Radiant Flux	ASTM E648	Class I
Smoke Density	ASTM E662	Pass
Impact Insulation Class IIC	ASTM E492*	
Sound Transmission Class STC	ASTM E90*	

^{*}The flooring assembly dictates IIC, STC, HIIC, and Low IIC results; contact your representative for specific testing.

Health & Environmental

FloorScore SCS Certified

Phthalate Free
















Warranty

5 Year Light Commercial, 5 Year Multifamily, 25 Year Residential

Accessories

Trims: T Mold, Reducer, End Cap, Stair Nose, Quarter Round **QNose** Stair Nosing

Layout Options:

