

GLUE DOWN | 2.5 MM, 20 MIL



Mead | DJLV0101Z



Grove | DJLV0102



Cadet | DJLV0104Z



Sawyer | DJLV0109



Haywood | DJLV0110



Montour | DJLV0111

SPECIFICATIONS

Construction	Solid Luxury Vinyl
Classification	ASTM F1700, Class III, Type B
Dimensions	7" Wide x 48" Long, 177.8 mm x 1219.2 mm
Overall Thickness	2.5 mm
Wear Layer	20 mil
Finish Coat	Polyurethane Glass Bead
Texture	Embossed
Edge Profile	4-Sided Square Edge
Packaging	42.03 sf/ctn, 50 ctn/plt, 2101.5 sf/plt
Installation	Glue Down
Warranty	10 Year Light Commercial/MultiFamily Common Areas, 30 Year Residential

INSTALLATION FAST FACTS

- Acclimate to Normal Room Conditions (NRC) 65°F - 85°F
- Expansion Space: 1/4" gap
- Ambient RH Between 35% to 60%
- Work out of several boxes, mixing product for visual appearance
- Minimum 3500 PSI for Concrete/Cypcrete Substrates

Read Complete Instructions Before Installing



tascontract.com

**SPEC SHEET
WARRANTY
INSTALLATION & MAINTENANCE**
[QNOSE](#)

