

# LEVELS 5.0

LOOSE LAY | 5.0 MM, 20 MIL



**True** | NOLL52002



**Horizon** | NOLL52004



**Plane** | NOLL520T1



**Balance** | NOLL52003



**Even** | NOLL52001



**Grade** | NOLL52005



**Uniform** | NOLL52006



**Align** | NOLL520T2



**Above** | NOLL52007



**Below** | NOLL52008

## SPECIFICATIONS

Construction	Luxury Vinyl Tile
Classification	ASTM F1700, Class III, Type A
Dimensions	Plank: 9.25" Wide x 59.25" Long Tile: 18" Wide x 36" Long
Overall Thickness	5.0 mm (including non-skid backing)
Wear Layer	20 mil
Finish Coat	EnduraGuard
Texture	Embossed
Edge Profile	Beveled Edge
Packaging	27 sf/ctn, 36 ctn/plt, 972 sf/plt, 6 pcs/ctn, 46.3 lbs wt/ctn
Installation	Loose Lay or Full Spread Glue
Warranty	10 Year Commercial

## INSTALLATION FAST FACTS

- Acclimate to Normal Room Conditions (NRC) 65°F - 85°F
- Expansion Space: 1/4" gap
- Ambient RH Between 35% to 60%
- Work out of several boxes, mixing product for visual appearance
- Minimum 3500 PSI for Concrete/Cypcrete Substrates

Read Complete Instructions Before Installing



tascontract.com

**SPEC SHEET  
WARRANTY  
INSTALLATION & MAINTENANCE**  
[QNOSE](#)

