

LEVELS 5.0

LOOSE LAY | 5.0 MM, 20 MIL



True | NOLL52002



Horizon | NOLL52004



Plane | NOLL520T1



Balance | NOLL52003



Even | NOLL52001



Grade | NOLL52005



Uniform | NOLL52006



Align | NOLL520T2



Above | NOLL52007



Below | NOLL52008

SPECIFICATIONS

Construction	Luxury Vinyl Tile
Classification	ASTM F1700, Class III, Type A
Dimensions	Plank: 9.25" Wide x 59.25" Long Tile: 18" Wide x 36" Long
Overall Thickness	5.0 mm (including non-skid backing)
Wear Layer	20 mil
Finish Coat	EnduraGuard
Texture	Embossed
Edge Profile	Beveled Edge
Packaging	Plank: 22.84 sf/ctn, 64 ctn/plt, 1,461.76 sf/plt Tile: 27 sf/ctn, 36 ctn/plt, 972 sf/plt
Installation	Loose Lay or Full Spread Glue
Warranty	10 Year Commercial

INSTALLATION FAST FACTS

- Acclimate to Normal Room Conditions (NRC) 65°F - 85°F
- Expansion Space: 1/4" gap
- Ambient RH Between 35% to 60%
- Work out of several boxes, mixing product for visual appearance
- Structurally Sound

Read Complete Instructions Before Installing



tascontract.com

SPEC SHEET
WARRANTY
INSTALLATION & MAINTENANCE
[QNOSE](#)

