
BOREALIS BEYOND

PACIFIC SUMMIT

SPC | 7.0 MM, 20 MIL

Construction	SPC Waterproof Core Vinyl Click
Classification	ASTM F3261
Dimensions	7" x 60"
Overall Thickness	7.0 mm (includes 1.5 mm IXPE pad)
Wear Layer	20 mil
Finish	Polyurethane
Texture	Embossed
Edge Profile	Painted Bevel
Packaging	17.915 sf/ctn, 6 pcs/ctn, 43.5 lbs/ctn, 55 ctn/plt, 985.33 sf/plt



Installation & Maintenance

Angle / Angle

Transition Required for rooms Larger than: (50) L x (50) W
Minimum expansion space to all vertical substrates 1/4"

Ambient & Surface Temperature at Installation: 60 - 85 Degrees Fahrenheit

Maintenance: Neutral pH Cleaner

Test Method & Requirements

Resilient Floor in Modular Format	ASTM F3261	Pass
Thickness (with Pad)	ASTM F386/387	Pass
Wear Layer Thickness	ASTM F410	Pass
Stain/Chemical Resistance	ASTM F925	Pass
Resistance to Heat Color Change	ASTM F1514	Pass
Resistance to Light Color Change	ASTM F1515	Pass
Residual Indentation	ASTM F1914	Pass
Size & Squareness	ASTM F2055	Pass
Dimensional Stability	ASTM F2199	Pass
Dimensional Stability w/Exposure to Heat	ISO 23999	Pass
Determination of Geometrical Characteristics	ISO 24337	Pass
Static Coefficient of Friction Polished Surface	ASTM D2047	Exceeds
Static Load Limit	ASTM F970	0.005 in or less 2,000 psi
Flammability/Radiant Flux	ASTM E648	Class I
Smoke Density	ASTM E662	Pass
Impact Insulation Class IIC	ASTM E492*	
Sound Transmission Class STC	ASTM E90*	

*The flooring assembly dictates IIC, STC, HIIC, and Low IIC results; contact your representative for specific testing.

Health & Environment

FloorScore SCScertified


Warranty

30 Year Residential, 10 Year Multifamily,10 Year Light Commercial


Accesories

End Cap, Quarter Round, Stair Nose, Reducer, T-mold, Q Nose

Layout Options:



ASHLAR



STAGGER

floor score SCScertified

PHTHALATE FREE

WATER PROOF

STOCKED IN KENT

RADIANT HEAT APPROVED