# SILENT STRIDE



# SPC | 8.5 MM, 20 MIL

Construction	SPC Rigid Core, Stone Polymer Composite		
Classification	ASTM F3261, Class 1, Type B, Grade 1, Class B		
Dimensions	9" Wide x 60" Long, 225 mm x 1,422 mm		
Overall Thickness	8.5 mm (Includes 1.0 mm Pad)		
Attached Pad	1.0 mm IXPE		
Wear Layer	20 Mil		
Finish Coat	Polyurethane Adamantine Finish		
Texture	Embossed		
Edge Profile	4-Sided Micro Bevel		
Packaging	14.53 sf/ctn, 4 pcs/ctn, 41 lbs/ctn, 56 ctn/plt, 813.68 sf/plt		

#### Installation & Maintenance

Angle / Angle

Layout Room Size: Minimum expansion space to all vertical substrates 1/4".

Transition required for rooms larger than 50' W x 50' L.

Ambient & Surface Temperature at installation: 60 - 85 degrees Fahrenheit

Maintenance: Neutral pH Cleaner, such as Fresh Floors by TAS Flooring.

Test Method & Requirements			
Resilient Floor in Modular Format	ASTM F3261	Pass	
Thickness (with Pad)	ASTM F386/387	Pass	
Wear Layer Thickness	ASTM F410	Pass	
Stain/Chemical Resistance	ASTM F925	Pass	
Resistance to Heat Color Change	ASTM F1514	Pass	
Resistance to Light Color Change	ASTM F1515	Pass	
Residual Indentation	ASTM F1914	Pass	
Size & Squareness	ASTM F2055	Pass	
Dimensional Stability	ASTM F2199	Pass	
Dimensional Stability w/Exposure to Heat	ISO 23999	Pass	
Determination of Geometrical Characteristics	ISO 24337	Pass	
Static Coefficient of Friction Polished Surface	ASTM D2047	Exceeds	
Flammability/Radiant Flux	ASTM E648	Class I	
Smoke Density	ASTM E662	Pass	
Impact Insulation Class IIC	ASTM E492*		
Sound Transmission Class STC	ASTM E90*		

<sup>\*</sup>The flooring assembly dictates IIC, STC, HIIC, and Low IIC results; contact your representative for specific testing.

## Health & Environmental

FloorScore SCS Certified

Phthalate Free














#### Warranty

10 Year Light Commercial, 10 Year Multifamily, 30 Year Residential

### Accessories

Trims: T Mold, Reducer, End Cap, Stair Nose, Quarter Round QNose Stair Nosing

