EVERECO



PVC-FREE GLUE DOWN | 2.5 MM

Construction	PVC-Free Resilient Planks & Tiles	
Classification	ASTMF3404	
Dimensions (nominal)	Wood: 7" Wide x 48" Long, 177.8 mm x 1219.2 mm	
	Stone: 12" Wide x 24" Long, 308.8 mm x 609.6 mm	
Overall Thickness	2.5 mm	
Finish Coat	PVC-Free Polyurethane and	
	Thermoplastic Polyurethane	
Texture	Embossed	
Edge Profile	Square Edge	
Packaging	Wood: 35 sf/ctn, 15 pcs/ctn, 30.5 lbs/ctn, 60 ctn/plt, 2100 sf/plt	
	Stone: 36 sf/ctn, 18 pcs/ctn, 31.3 lbs/ctn, 60 ctn/plt, 2160 sf/plt	

Installation & Maintenance

Glue Down


Ambient & Surface Temperature at Installation: Acclimate product to environment.

Maintenance: Subfloors dry and flat (3/16" in 10'). Approved over in-floor Radiant Heat, all methods. Max temp. 85 degrees.

Recommended Adhesives: Taylor Adhesive Dynamic (preferred), Taylor Pinnacle, or TEC Flexera High Track Premium Universal Adhesive. Please see Installation Instructions for full application requirements.

Test Method & Requirements			
Heterogeneous Polyurethane Flooring (PVC Free)	ASTM F3404		
Flexibility	ASTM F137	Pass	
Thickness	ASTM F386	Pass	
Wear Layer Thickness	ASTM F410	Pass	
Stain/Chemical Resistance	ASTM F925	Pass	
Static Load Recovery > 250 Lbs	ASTM F970	Pass	
Resistance to Heat / Light	ASTM F1514-15	Pass	
Residual Indentation	ASTM F1914	Pass	
Size & Squareness	ASTM F2055	Pass	
Dimensional Stability	ASTM F2199	Pass	
Measuring of Resilient by Dial Gauge	ASTM F2421	Pass	
Castor Chair Test	ISO 4918	Pass	
Static COF Polished Surface	ASTM D2047	Exceeds Industry Standard	
Flammability/Radiant Flux	ASTM E648	Class i	
Smoke Density	ASTM E662	Pass	
*The fire size and the distance UC CTC LUIC and Low UC and the same state of the size and the size			

^{*}The flooring assembly dictates IIC, STC, HIIC, and Low IIC results; contact your representative for specific testing.




TPU = Thermoplastic Polyurethane

Warranty

10 Year Commercial, 10 Year Light Commercial, 25 Year Residential

Layout Options: NOT TO SCALE HERRINGBONE TRIPLE HERRINGBONE FIVE PLANK PARQUET



Health & Environmental

FloorScore SCS Certified
Phthalate-Free
PVC-Free
100% Recyclable
100% Thermoplastic PU
Declare Red List Free Verified
Health Product Declaration (HPD) Verified











