DEL MAR

TAS FLOORING

HARDWOOD | 7/16" THICK



Burkshires | HFDMO7167BK



Calabazas | HFDMO7167CS



Irwindale | HFDMO7167ID



Napa | HFDMO7167NP

SPECIFICATIONS

Construction	Engineered Multi-Layer Parque
Species	White Oak
Dimensions	7.5" Wide x Random Lengths up to 75"
Overall Thickness	7/16"
Attached Pad	N/A
Veneer Thickness:	1.5 mm Veneer Over Multiply Core
Surface Finish	High Performance UV Cured Urethane
Design Feature	Thermal Enhanced, Brushed
Edge Profile	4-Sided Micro Bevel
Packaging	34.3 sf/carton - 50 carton/pallet - 1715 sf/pallet
Installation	Nail Down/Glue/Float
Warranty	Lifetime Structure, 30 Yr Residential

INSTALLATION FAST FACTS

- Acclimate product to normal room conditions
- Moisture Content: Is recommended 7% to 9% (Not to exceed 11%)
- Relative Humidity: 40%-55%
- Expansion Space: 7/16" gap
- Recommended Room Temp: 65˚F -75˚F after install

Read Complete Instructions Before Installing

tascontract.com

SPEC SHEET
WARRANTY
INSTALLATION & MAINTENANCE
TRIMS, TRANSITIONS & QNOSE

floor score
SCScertified

CARB PHASE 2 COMPLIANT

Multi-Length Planks

Thermal Enhanced

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

Additional specifications, full installation instructions & warranty information available online at **tasflooring.com**

A division of T&A supply company, Inc.