

SILVERADO



GLUE DOWN | 5.0 MM, 20 MIL



Bandera | WILV0301



Bannack | WILV0302



Grafton | WILV0303



Talon | WILV0304



Oatman | WILV0305



Oxridge | WILV0306



Bodie | WILV0307



Moraga | WILV0311



Belvedere | WILV0314



Granville | WILV0316

SPECIFICATIONS

Construction	Glue Down Luxury Vinyl
Dimensions	7" Wide x 48" Long, 177.8 mm x 1220 mm
Overall Thickness	5.0 mm
Wear Layer	20 mil
Finish	Premium Adamantine Finish™
Texture	Embossed
Edge Profile	Micro Bevel Edge
Installation	Glue Down
Warranty	30 Yr Residential/Multi-Family Residence, 10 Yr Commercial/Multi-Family Common Areas
Packaging	21.013 sf/carton - 50 carton/pallet - 1050.65 sf/pallet

INSTALLATION FAST FACTS

- Acclimate to Normal Room Conditions (NRC) 60°F - 85°F, RH Between 35% - 55%
- Do not net or compression fit
- Minimum 3500 PSI for Concrete/Gypsum
- Hydro Radiant Heat approved (≤ 85°F)
- Roll flooring immediately after installation in two directions, reroll 2 hours later
- Follow adhesive instructions for substrate moisture, coverage, PH, porosity, and open time
- Repair or replace worn trowel notches
- Insure floor flatness to within 1/8" in 6'

Read Complete Instructions Before Installing



**SPEC SHEET
WARRANTY
INSTALLATION & MAINTENANCE**

tasflooring.com



Additional Specifications, Full Installation Instructions & Warranty Information Available Online

tasflooring.com | a division of **TAS** supply company, Inc. Feb 2025