

# SIERRA TILE

SPC | 6 MM, 12 MIL



**Cotto Beige** | DGRC1401



**Limestone White** | DGRC1402



**Hermes Gray** | DGRC1403



**Pulpis Brown** | DGRC1404



**Sand White** | DGRC1405



**Italian Grey Sand** | DGRC1406

## SPECIFICATIONS

Construction	Rigid Polymeric Core Waterproof
Classification	ASTM F3261, Class I, Type B, Grade 1, Class B
Dimensions	12" Wide x 24" Long (300 mm x 600 mm)
Overall Thickness	6.0 mm (Includes 1.0 mm Pad)
Attached Pad	1.0 mm
Wear Layer	12 mil
Finish Coat	Polyurethane
Texture	Embossed
Edge Profile	Painted Bevel
Packaging	19.375 sf/carton - 54 carton/pallet - 1046.25 sf/pallet
Installation	Angle/Angle
Warranty	25 Yr Residential, 5 Yr Commercial, 5 Yr Multifamily

## INSTALLATION FAST FACTS

- No Transitions in under 2,500 sf
- Acclimate to Normal Room Conditions (NRC) 65°F - 85°F
- Hydro Radiant Heat approved (≤ 85°F)
- Expansion Space: 1/4" gap
- Ambient RH Between 35% to 60%
- Work out of several boxes, mixing product for visual appearance
- Hydro Radiant Heat approved (≤ 85°F)

Read Complete Instructions Before Installing



tasflooring.com

**SPEC SHEET WARRANTY  
INSTALLATION & MAINTENANCE  
TRIMS, TRANSITIONS & QNOSE**

