

WATERPROOF LAMINATE AC4 | 12 MM + 2.0 MM PAD



Sceptor | CHPL3241



Bolden | CHPL3248



Valor | CHPL3255



Aspire Bay | CHPL3258



Cameo Crest | CHPL3260



Fortress | CHPL3262



Noble View | CHPL3272



Fairchild | CHPL3275

SPECIFICATIONS

Construction	Waterproof Laminate
Classification	EN13329
Dimensions	9" Wide x 60" Long (231 mm x 1525 mm)
Overall Thickness	14 mm (Includes 2.0 mm IXPE Pad)
Finish	Ultra Matte
Wear Surface	AC4 Rating
Texture	Embossed-In-Register
Edge Profile	4-Sided Painted Bevel
Packaging	18.94 sf/ctn, 5 pcs/ctn, 43.6 lbs/ctn, 52 ctn/plt, 984.9 sf/plt
Installation	Angle/Angle
Warranty	Waterproof, 15 Year Light Commercial, Lifetime Residential

INSTALLATION FAST FACTS

- Radiant Heat: Approved (Hydro Systems ONLY)
- Acclimate product to normal room conditions
- Leave 3/8" expansion for areas over 25'
- Transitions required for rooms larger than 45'L or 45"W
- Subfloors dry and flat (3/16" in 10')
- Installation on or below grade concrete requires 6 mil moisture barrier

Read Complete Instructions Before Installing



tasflooring.com

SPEC SHEET, WARRANTY
INSTALLATION & MAINTENANCE

