

GLUE DOWN | 3.0 MM, 20 MIL



Balboa | NOLV0201



Monaco | NOLV0202



Capetown | NOLV0203



Havana | NOLV0204



Sorrento | NOLV0205



Zurich | NOLV0206



Oria | NOLV0207



Lisbon | NOLV0208

SPECIFICATIONS

Construction	Luxury Vinyl Tile
Classification	ASTM F1700, Class III, Type B
Dimensions	7.25" Wide x 48" Long
Overall Thickness	3.0 mm
Wear Layer	20 mil
Finish Coat	Polyurethane Glass Bead
Texture	Embossed-In-Register
Edge Profile	4-Sided Micro-Bevel
Packaging	34.90 sf/ctn, 50 ctn/pal, 1745 sf/plt, 40 lbs/ctn
Installation	Glue Down
Warranty	10 Yr Commercial/Multifamily Common areas, 30 Yr Residential/Multifamily Residence

INSTALLATION FAST FACTS

- Acclimate to Normal Room Conditions (NRC) 65°F - 85°F
- Expansion Space: 1/4" gap
- Ambient RH Between 35% to 60%
- Work out of several boxes, mixing product for visual appearance

Read Complete Instructions Before Installing



SPEC SHEET
WARRANTY
INSTALLATION & MAINTENANCE

tasflooring.com

