## PROVINCIAL ESTATE



## SPC | 6.0 MM, 20 MIL



Idle Hour | DGRC0802



Lynnewood | DGRC0804



Meadow Brook | DGRC0805



Florham | DGRC0806



Fairlawn | DGRC0808



Eden Park | DGRC0810



Wembley | DGRC0809



Southwark | DGRC0811

## **SPECIFICATIONS**

Construction	SPC Rigid Core, Stone Polymer Composite
Classification	ASTM F3261, Class 1, Type B, Grade 1, Class B
Dimensions	7" Wide x 60" Long (180 mm x 1524mm)
Overall Thickness	6.0 mm (Includes 1 mm IXPE pad)
Wear Layer	20 mil
Finish Coat	High-Definition, Low Gloss Matte
Texture	Embossed-In-Register
Edge Profile	4-Sided Painted Bevel
Packaging	23.62 sf/ctn, 8 pcs/ctn, 50.5 lbs/ctn, 45 ctn/plt, 1062.9 sf/plt
Installation	Angle/Angle
Warranty	10 Yr Light Commercial, 10 Yr Multifamily, 30 Yr Residential

## floor score









**INSTALLATION FAST FACTS** 

- Transitions required for rooms larger than 50' W x 50' L
- Acclimate to Normal Room Conditions (NRC) 60°F 85°F
- Hydro Radiant Heat approved (≤ 85°F)
- Expansion Space: 1/4" gap
- Ambient RH Between 35% to 55%
- Floor Flatness to 3/16" in 10'
- Floating floors must be allowed to expand and contract with no restrictions

Read Complete Instructions Before Installing



SPEC SHEET
WARRANTY
INSTALLATION & MAINTENANCE
TRIMS, TRANSITIONS & <u>QNOSE</u>

tasflooring.com