
NOBILITY

TAS FLOORING

GLUE DOWN | 2.5 MM, 12 MIL

Construction	Solid Vinyl Tile
Classification	ASTM F1700, Class III, Type B
Dimensions	7" Wide x 48" Long (177.8 mm x 1219.2 mm)
Overall Thickness	2.5 mm
Wear Layer	12 mil
Finish Coat	Polyurethane
Texture	Embossed
Edge Profile	Square
Packaging	35 sf/ctn, 15 pcs/ctn, 30.5 lbs/ctn, 60 ctn/plt, 2100 sf/plt



Installation & Maintenance

Glue Down

Ambient & Surface Temperature at Installation: 60 - 85 Degrees Fahrenheit

Maintenance: No Wax, Neutral PH cleaner, such as TAS Flooring Fresh Floors.

Recommended Adhesive: WF Taylor Dynamic, Uzin KE39.
For Heavy Loads use WF Taylor Pinnacle

Test Method & Requirements

Solid Vinyl Floor Tile	ASTM F1700	Pass
Flexibility	ASTM F137	Pass
Thickness	ASTM F386	Pass
Wear Layer Thickness	ASTM F410	Pass
Resistance to Heat Color Change	ASTM F1514	Pass
Resistance to Light Color Change	ASTM F1515	Pass
Residual Indentation	ASTM F1914	Pass
Size & Squareness	ASTM F2199	Pass
Static Coefficient of Friction Polished Surface	ASTM D2047	Exceeds Standard
Static Load Limit	ASTM F970	Pass > 250 LBS
Flammability/Radiant Flux	ASTM E648	Class I
Smoke Density	ASTM E662	Pass

Health & Environmental

FloorScore® program by SCS Global Services
Environmental Product Declaration (EPD)

Warranty


5 Year Light Commercial, 5 Year Multifamily, 25 Year Residential


Accessories


QNose Stair Nosing


Layout Options:


NOT TO SCALE


HERRINGBONE


TRIPLE HERRINGBONE


FIVE PLANK PARQUET


ASHLAR


STAGGER

floor score SCScertified

CERTIFIED ENVIRONMENTAL PRODUCT DECLARATION UL.COM/EPD

PHTHALATE FREE

Hydronic Heat

Glue