

GLUE DOWN | 5.0 MM, 20 MIL



**Lona** | VRLV0101



**Sandoval** | VRLV0102



**Churchill** | VRLV0103



**Banderin** | VRLV0104



**Forsyth** | VRLV0105



**Logan** | VRLV0106



**Rockbridge** | VRLV0107



**Kodiak** | VRLV0108

## SPECIFICATIONS

Construction	Luxury Vinyl Plank
Classification	ASTM F1700, Class III, Type B
Dimensions	7.25" Wide x 48" Long (185 mm x 1226 mm)
Overall Thickness	5.0 mm
Wear Layer	20 mil
Finish Coat	Polyurethane
Texture	Embossed
Edge Profile	Micro Bevel
Packaging	21.97 sf/ctn, 9 pcs/ctn, 41.2 lbs/ctn, 55 ctn/plt, 1208.5 sf.plt
Installation	Glue Down, Loose-Lay
Warranty	10 Year Light Commercial, 30 Year Multifamily Residence, Lifetime Residential

## INSTALLATION FAST FACTS

- Acclimate to Normal Room Conditions (NRC) 65°F - 85°F
- Expansion Space: 1/4" gap
- Ambient RH Between 35% to 60%
- Work out of several boxes, mixing product for visual appearance
- Structurally Sound

Read Complete Instructions Before Installing



tasflooring.com

**SPEC SHEET  
WARRANTY  
INSTALLATION & MAINTENANCE**

