ODYSSEY EG

TAS FLOORING

GLUE DOWN | 3.0 MM, 20 MIL

Construction	Luxury Vinyl Plank
Classification	ASTM F1700
Dimensions	7.25" Wide x 48" Long (180 mm x 1200 mm)
Overall Thickness	3.0 mm
Wear Layer	20 mil
Finish Coat	ENDURAGUARD SURFACE PROTECTION
Texture	Embossed
Edge Profile	Square
Packaging	34.9 sf/ctn, 15 pcs/ctn, 34 lbs/ctn, 50 ctn/plt, 1745 sf/plt



Installation & Maintenance

Glue Down

Ambient & Surface Temperature at Installation: 60 - 85 Degrees Fahrenheit

Maintenance: A neutral pH cleaner, such as Fresh Floors by TAS Flooring.

Recommended Adhesive: WF Taylor Dynamic, Uzin KE39.
For Heavy Loads use WF Taylor Pinnacle

Test Method & Requirements

Solid Vinyl Floor Tile	ASTM F1700	Pass
Flexibility	ASTM F137	Pass
Thickness	ASTM F386	Pass
Wear Layer Thickness	ASTM F410	Pass
Resistance to Heat Color Change	ASTM F1514	Pass
Resistance to Light Color Change	ASTM F1515	Pass
Residual Indentation	ASTM F1914	Pass
Size & Squareness	ASTM F2199	Pass
Static Coefficient of Friction Polished Surface	ASTM D2047	Exceeds Standard
Static Load Limit	ASTM F970	Pass > 250 LBS
Flammability/Radiant Flux	ASTM E648	Class I
Smoke Density	ASTM E662	Pass
Slip Resistance	DIN 51130	Angle: 18.7° Rating: R10

Health & Environmental

FloorScore® program by SCS Global Services
Environmental Product Declaration (EPD)
Health Product Declaration (HPD)

Warranty

10 Year Commercial, 10 Year Multifamily Common Areas,
30 Year Residential/Multifamily Residence

Layout Options:

NOT TO SCALE





floor score
SCScertified
CERTIFIED ENVIRONMENTAL PRODUCT DECLARATION UL.COM/EPD
Health Product DECLARATION™