

SPC | 5.0 MM, 12 MIL



**Chalus Hazelwood** | PPRC0101



**Davos Oak** | PPRC0102



**Fenwick Oak** | PPRC0103



**Sara Birch** | PPRC0104



**Tropical Acacia** | PPRC0105



**Wooden Oak** | PPRC0106



**Beacon Oak** | PPRC0107



**Alcove Oak** | PPRC0108



**Medallion Oak** | PPRC0109



**Nordland Hickory** | PPRC0110



**Collins** | PPRC0111

## SPECIFICATIONS

Construction	SPC Rigid Waterproof Core Vinyl Click
Classification	ASTM F3261
Dimensions	7" wide x 48" long, 182 mm x 1220 mm
Overall Thickness	5 mm (includes 1 mm IXPE Pad)
Wear Layer	12 mil
Finish Coat	Polyurethane
Texture	Embossed
Edge Profile	4-Sided Micro Bevel
Packaging	28.68 sf/ctn, 55 ctn/plt, 1577.4 sf/plt
Installation	Angle/Angle
Warranty	5 Year Light Commercial, 25 Year Multifamily (units), 5 Year Multifamily (common areas) & 25 Year Residential

## INSTALLATION FAST FACTS

- Radiant Heat: Approved (Hydro Systems ONLY)
- Acclimate product to normal room conditions
- Recommended Room Temp: 60°F-85°F after install
- Expansion Space: 1/4" gap
- Transition required for rooms larger than 50'W x 50'L
- Subfloors dry and flat (3/16" in 10')

**Read Complete Instructions Before Installing**



tasflooring.com

**SPEC SHEET  
WARRANTY  
INSTALLATION & MAINTENANCE  
TRIMS, TRANSITIONS & QNOSE**

