AMBIANCE

TAS FLOORING

LSPC - ABA | 10 MM, 20 MIL



Maestro | WIRC0601



Bacchus | WIRC0602



Orion | WIRC0603



Virtuoso | WIRC0605



Provost | WIRC0607



Aurelius | WIRC0609



Apollo | WIRC0610



Fortingall | WIRC0611

SPECIFICATIONS

Construction	LSPC Hybrid - ABA Foam Rigid Core
Classification	ASTM F3261, Class 1, Type B, Grade 1, Class B
Dimensions	7.125" Wide x 60" Long
Overall Thickness	10 mm (includes 2 mm IXPE Pad)
Wear Layer	20 mil
Finish Coat	Low Gloss Polyurethane with Adamantine Finish
Texture	Embossed
Edge Profile	4-Sided Painted Bevel
Packaging	23.75 sf/ctn, 8 pcs/ctn, 56 lbs/ctn, 30 ctn/plt, 712.5 sf/plt
Installation	Angle / Angle, Float
Warranty	10 Year Light Commercial, 10 Year Multifamily, 30 Year Residential

INSTALLATION FAST FACTS

- Transitions required for rooms larger than 50' W x 50' L
- Acclimate to Normal Room Conditions (NRC) 60°F - 85°F
- Hydro Radiant Heat approved (≤ 85°F)
- Expansion Space: 1/4" gap
- Ambient RH Between 35% to 55%
- Floor Flatness to 3/16" in 10'
- Floating floors must be allowed to expand and contract with no restrictions

Read Complete Instructions Before Installing

tascontract.com

SPEC SHEET
WARRANTY
INSTALLATION & MAINTENANCE
TRIMS, TRANSITIONS & QNOSE

GREENGUARD GOLD | floor score SCScertified | PHTHALATE FREE | Hydronic Heat | Waterproof | Floating Angle/Angle | Anti-microbial | Adamantine Finish™

TAS CONTRACT

Additional specifications, full installation/maintenance and warranty information available online at **TASCONTRACT.COM**.

T&A supply company, Inc.