

Bastion & Turret Interlocking Tiles



Figure 1 Bastion Tile



Figure 2 Turret Tile

I. General Information

Bastion and Turret tiles provide remarkable dirt and moisture removal. Heavy duty construction is designed specifically for entryways with high density foot traffic. It performs best in weather protected areas.

This product must be installed by professional installers that have sufficient professional liability insurance coverage (aka Errors and Omissions Insurance) for the project. Matter Surfaces recommends installing and maintaining entrance matting at all outdoor entrances; this will improve air quality, reduce maintenance costs, and lengthen the life of your floors.

Proper glides must be used on all furniture that may slide directly across the floor, consult the furniture manufacturer for recommendations for use on resilient flooring. Heavy objects must not be moved directly across the floor; use protective boards.

Direct sunlight can cause UV damage (fading or bleaching) to most interior finishes, so Low E glass should be selected that will reduce the UV transmission to less than 1%. If not, applying 3M™ protection film (or similar) on the windows is recommended.

Do not install any material that has visible defects or damage. A contractor that installs any material that has visible defects or damage assumes responsibility for the damaged material. All Safety Data Sheets (SDS) and Installation, Maintenance and Warranty requirements must be read, understood and followed.

These instructions supersede any verbal or written instructions from Matter Surfaces representatives and must be followed for the limited warranty to be in effect.

Technical Documentation

Tile size	14.5" x 8" (2.25 sf per tile)
Thickness	11 mm (0.42")
Composition	UV-resistant vinyl/NBR
Insert Pile Material	100% polyamide
Color	Black
Weight	1.5 lbs./sqft
Packaging	14 tiles / pkg (10.76 sqft)
Limited Warranty	2 years