ALTA VISTA

TAS FLOORING

HARDWOOD | 5/8" THICK



Apollo | HFAVO587AP



Fermont | HFAVO587FM



Santa Rosa | HFAVO587SR



Veranda | HFAVO587VD

SPECIFICATIONS

Construction	Engineered Multi-Layer Parque
Species	Engineered European White Oak
Dimensions	7.5" Wide x Random Lengths up to 75"
Overall Thickness	5/8"
Attached Pad	N/A
Veneer Thickness:	3.0 mm Sawn-Cut Veneer over Multiply Core
Surface Finish	High Performance UV Cured Urethane
Design Feature	Thermal Enhanced, Brushed
Edge Profile	4-Sided Bevel
Packaging	23.5 sf/ctn, 50 ctn/plt, 1175 sf/plt
Installation	Glue/Float/Staple (Glue Assist)
Warranty	10 Yr Light Commercial, 30 Yr Residential, Limited Lifetime Structural

INSTALLATION FAST FACTS

- Acclimate product to normal room conditions
- Moisture Content: Is recommended 7% to 9% (Not to exceed 11%)
- Relative Humidity: 40%-55%
- Expansion Space: 7/16" gap
- Recommended Room Temp: 65˚F -75˚F after install

Read Complete Instructions Before Installing

tasflooring.com

SPEC SHEET
WARRANTY
INSTALLATION & MAINTENANCE
TRIMS, TRANSITIONS & QNOSE

floor score
SCScertified

CARB PHASE 2 COMPLIANT

Multi-Length Planks

Thermal Enhanced

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

Additional specifications, full installation instructions & warranty information available online at **tasflooring.com**

T&A supply company, Inc.