

# ALTA VISTA



HARDWOOD | 5/8" THICK



**Apollo** | HFAVO587AP



**Fermont** | HFAVO587FM



**Santa Rosa** | HFAVO587SR



**Veranda** | HFAVO587VD

## SPECIFICATIONS

Construction	Engineered Multi-Layer Parquet
Species	Engineered European White Oak
Dimensions	7.5" Wide x Random Lengths up to 75"
Overall Thickness	5/8"
Attached Pad	N/A
Veneer Thickness:	3.0 mm Sawn-Cut Veneer over Multiply Core
Surface Finish	High Performance UV Cured Urethane
Design Feature	Thermal Enhanced, Brushed
Edge Profile	4-Sided Bevel

## INSTALLATION FAST FACTS

- Acclimate product to normal room conditions
- Moisture Content: Is recommended 7% to 9% (Not to exceed 11%)
- Relative Humidity: 40%-55%
- Expansion Space: 7/16" gap
- Recommended Room Temp: 65° F -75° F after install

Read Complete Instructions Before Installing



tasflooring.com

**SPEC SHEET  
WARRANTY  
INSTALLATION & MAINTENANCE  
TRIMS, TRANSITIONS & QNOSE**



Additional specifications, full installation instructions & warranty information available online at [tasflooring.com](https://tasflooring.com)

**TAS** supply company, Inc.