

TITAN WOOD



HYBRID HARDWOOD | 7.2 MM, 1.2 MM



Hyperian | WBTIH12



Cronus | WBTIH13



Oceanus | WBTIOA10



Tethys | WBTIOA18



Rhea | WBTIOA19



Themis | WBTIOA21

SPECIFICATIONS

Construction	Waterproof Hybrid Hardwood
Species	American Hickory, European White Oak
Dimensions	7.5" Wide x 75" Long, 190 mm x 1900 mm
Overall Thickness	7.2 mm (includes pad)
Attached Pad	1.0 mm Premium IXPE Pad
Veneer Thickness:	1.2 mm
Surface Finish	Titan Tough wear layer with aluminum oxide
Design Feature	Brushed
Edge Profile	4 Sided Micro Bevel

INSTALLATION FAST FACTS

- Acclimate product to normal room conditions
- Moisture Content: Is recommended 7% to 9% (Not to exceed 11%)
- Relative Humidity: 40%-55%
- Expansion Space: 7/16" gap
- Recommended Room Temp: 65° F -75° F after install

Read Complete Instructions Before Installing



tasflooring.com

**SPEC SHEET
WARRANTY
INSTALLATION & MAINTENANCE
TRIMS, TRANSITIONS & [QNOSE](#)**



Additional specifications, full installation instructions & warranty information available online at tasflooring.com

T&A supply company, Inc.