WORLD

PRODUCT DETAILS

Product type / Construction	Wood Flooring / 3-layer engineered
Design / Wood species	3-strip / Brazilian Cherry
Surface Treatment	Silk matte finish
Features	Smooth
Width x Length x Thickness	7 7/8" inches x 95 3/8" inches x 15 mm
Weight per package / Weight per m² (kg)	60.63 lbs / 9.45 kg
Area per Package / Area per pallet	31.3 sqft / 1409.5 sqft
Grading	Calm
Joint	Woodloc® 5S
Installation method	Glue-Down, Floating
Floor heating	Yes
Wear-layer material / Wear Layer Thickness approx. (mm)	Hardwood / 3.5 mm
Resandable	2 times

PRODUCT DETAILS

Core material	Pine/Spruce lamella
Brinell value / Brinell Range	7,0 / 4.5 - 14.1
LRV / LRV Std1 / LRV Std2	20 / 2.4 / 4.8
Warranty	25 years
Warranty US	25 years
Collection	World Collection
Joint	Woodloc® 5S

TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimun Mean Density kg/m³		>500 kg/m³
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm²	EN1533	NPD
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Thermal Conductivity	EN12664	0,11W/mK
Slip resistance	CEN/TS15676	NPD

TSCA TITLE VI & CARB P2 Compliant

FSC www.fsc.org

Distributed by TA Supply

T&A supply company, Inc.