

UltraCare Smooth Silicone [NA]

Finishing Spray Solution for Smoothing of Sealants



DESCRIPTION

UltraCare[®] *Smooth Silicone* [NA] is a water-based, innovative spray solution suitable for silicone and urethane sealants as well as acrylic and latex caulks. It increases the speed and ease of finishing the sealant during application and contributes to creating smooth, compact surfaces that will reduce dirt pick-up and the formation of mold. It is suitable for use with sealants and caulks during installation of ceramic tile, porcelain tile, stone and glass tile.

FEATURES AND BENEFITS

- Ready to use
- Effective for use on silicone/urethane sealants and acrylic/latex caulks
- Increases the speed and ease of sealant application
- Helps with finishing and shaping of sealant joints
- Low-odor, low-VOC, water-based formula
- Non-residue formulation safe for ceramic, porcelain, stone and glass surfaces
- Non-corrosive; will not damage metal trims and profiles

WHERE TO USE

- Use on all change-of-plane and movement joints involving silicone/urethane sealants or acrylic/latex caulks around ceramic tiles, porcelain tiles, natural stone and glass tiles.

LIMITATIONS

- Do not dilute or mix with other chemicals or water.
- UltraCare Smooth Silicone* [NA] may not be suitable for use on other types of sealants not listed. Always test first to ensure the desired results.
- Do not allow the sealant or caulk to skin over before use.
- UltraCare Smooth Silicone* [NA] does not replace the need for proper preparation and protection of finish material and joint installation procedures. Follow all label instructions of the sealant manufacturer and industry standards for the best results.

PRODUCT APPLICATION

Before product use, take appropriate precautions. Refer to the Safety Data Sheet for details.

- Always test first in several inconspicuous areas to confirm desired results.
- Ensure that joints are full prior to use of *UltraCare Smooth Silicone* [NA].
- Spray directly on joints immediately after applying sealant or caulk before it starts to skin over, ensuring full coverage of the sealant or caulk.
- Finish joints using a suitable tool, being careful to remove all excess sealant or caulk.
- For best results on wide, textured or curved joints, a second application of *UltraCare Smooth Silicone* [NA] may be needed.

PROTECTION

- Do not allow to come in contact with any non-recommended surfaces.
- Keep container closed tightly when not in use.
- Store at room temperature in the original container.

Shelf Life and Product Characteristics

Shelf life	Up to 3 years when stored in original, unopened packaging at 73°F (23°C). Freeze/thaw-stable.
Appearance	Clear
Odor	Slight odor
Physical state	Liquid
VOC content (SCAQMD Rule 1113)	< 100 g per L
Typical VOC content per SCAQMD Rule 1113 testing methods	1 g per L

Packaging**Size**

Spray bottle: 24 U.S. oz. (710 mL)

Approximate Coverage*

per 24 U.S. oz. (710 mL)

Coverage

1,000 linear feet (305 m)

Coverage is heavily influenced by the type of sealant and the method of application.*ADDITIONAL INFORMATION**

Refer to the SDS for specific data related to health and safety as well as product handling.

For information on MAPEI's commitment to sustainability and transparency, as well as how MAPEI products may contribute to green building standards and certification systems, contact sustainability_USA@mapei.com (USA) or sustainability-durabilite@mapei.com (Canada).

WARNING

The test results shown in the TECHNICAL DATA table were obtained in compliance with test methods and curing cycles, if applicable, defined in the industry standards referenced on the Technical Data Sheet. Please note that the use of test procedures or methods other than those indicated in the table could lead to different values and that, in such cases, any liability of our company is excluded.

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement nor replace requirements per the TDS in effect at the time of the MAPEI product installation. For the most up-to-date TDS and warranty information, please visit our website at www.mapei.com. **ANY ALTERATIONS TO THE WORDING OR REQUIREMENTS CONTAINED IN OR DERIVED FROM THIS TDS SHALL VOID ALL RELATED MAPEI WARRANTIES.**

Before using, the user must determine the suitability of our products for the intended use, and the user alone assumes all risks and liability. **ANY CLAIM SHALL BE DEEMED WAIVED UNLESS MADE IN WRITING TO US WITHIN FIFTEEN (15) DAYS FROM DATE IT WAS, OR REASONABLY SHOULD HAVE BEEN, DISCOVERED.**

CONTACT INFORMATION

MAPEI Headquarters of North America

1144 East Newport Center Drive
Deerfield Beach, Florida 33442
1-888-US-MAPEI (1-888-876-2734) / (954) 246-8888

Technical Services

U.S. and Puerto Rico:
Flooring: 1-800-992-6273
Concrete and heavy construction: 1-888-365-0614
Canada:
1-800-361-9309

Customer Service

1-800-42-MAPEI (1-800-426-2734)

Edition Date: September 30, 2024 MK 3011019 (24-1932)

For the most current product data and BEST-BACKEDSM warranty information,
visit www.mapei.com.

All Rights Reserved. © 2024 MAPEI Corporation.

