LEVELS 2.5

TAS FLOORING

GLUE DOWN | 2.5 MM, 20 MIL



True | NOLV252002



Horizon | NOLV252004



Balance | NOLV252003



Even | NOLV252001



Grade | NOLV252005



Uniform | NOLV252006



Above | NOLV252007



Below | NOLV252008

SPECIFICATIONS

Construction	Luxury Vinyl Tile
Classification	ASTM F1700, Class III, Type A
Dimensions	7" Wide x 48" Long
Overall Thickness	2.5 mm
Wear Layer	20 mil
Finish Coat	ENDURAGUARD SURFACE PROTECTION
Texture	Embossed
Edge Profile	Square Edge
Packaging	2.5mm 35sf/ctn, 60 ctn/plt, 2100 sf/plt, 15pcs/ctn 30.4lbs wt/ctn
Installation	Glue Down
Warranty	10 Year Commercial

INSTALLATION FAST FACTS

- Acclimate to Normal Room Conditions (NRC) 65°F - 85°F
- Expansion Space: 1/4" gap
- Ambient RH Between 35% to 60%
- Work out of several boxes, mixing product for visual appearance

Read Complete Instructions Before Installing

tascontract.com

SPEC SHEET
WARRANTY
INSTALLATION & MAINTENANCE
QNOSE

floor score
SCScertified
PHTHALATE FREE
Hydronic Heat
Waterproof
Glue

Additional specifications, full installation/maintenance and warranty information available online at **TASFLOORING.COM**.

T&A supply company, Inc.